

Main Feature

1. 1 N/O & 1 C/O Contact
2. Sensitive coil 200mW.
3. Dielectric strength between coil & contact 4KV.
4. Low profile 10.5 mm.
5. Class I protection conforms to Industrial Norm, clearance and creepage more than 5.0 mm.
6. Cadmium-Free Contacts.
7. In accordance with IEC 60730-1.
8. Halogen Free series is available.



Contact Rating

Load Type	JE (DM)	JE (D)
Rated Load (Resistive)	8A 250VAC	5A 250VAC
	8A 30VDC	5A 30VDC
Max. Allowable Voltage	AC 440V	AC 380V
	DC 30V	DC 30V
Max. Allowable Current	8A	5A
Max. Allowable Power Force	2000VA	1,250VA
	240W	150W
Contact Material	Ag Alloy	Ag Alloy
Contact Form	SPST	SPDT

Application

1. Industrial Electronic Instrument, PLC, Timers, Temperature Control & Measure.
2. White goods.
3. Building Automation.
4. Air Conditioner.
5. Actuating Driver.


Performance (at Initial Value)

- Contact Resistance 100 mΩ Max. @1A,6VDC
- Operate Time..... 8 mSec. Max.
- Release Time 6 mSec. Max.
- Dielectric Strength:
 - Between Coil & Contact 4,000VAC at 50/60 Hz for one minute.
 - Between Contacts 1,000VAC at 50/60 Hz for one minute.
- Surge Strength 10,000V (between coil & contact 1.2x50μSec.)
- Insulation Resistance 100 MegaΩ Min. at 500VDC.
- Max. On/Off Switching:
 - Electrical..... 15 Cycles per Minute.
 - Mechanical 300 Cycles per Minute.
- Temperature Range..... -40~85°C

- Humidity Range..... 45~85% RH.
- Coil Temperature Rise..... 40°C Max.
- Vibration:
 - Endurance 10 to 55 Hz dual amplitude width 1.5mm.
 - Error Operation..... 10 to 55 Hz dual amplitude width 1.5mm.
- Shock:
 - Endurance 1,000m/S².
 - Error Operation..... 100 m/S².
- Life Expectancy:
 - Mechanical 10⁷ Operations at No load condition.
 - Electrical 10⁵ Operations at Rated Resistive Load.
- Weight about 6.0 g.

Safety Standard & Its File Number

- UL & C-UL E141060
- VDE 40013405



Coil Specification (at 20 °C)

Coil Sensitivity	Nominal Voltage (VDC)	Nominal Current (mA)	Coil Resistance ($\Omega \pm 10\%$)	Power Consumption (W)	Pull-In Voltage (VDC)	Drop-Out Voltage (VDC)	Maximum Allowable Voltage (VDC)
JE	3	66.7	45	Abt. 0.2	75% Maximum	5% Minimum	150%
	5	40.0	125				
	6	33.3	180				
	9	22.2	405				
	12	16.7	720				
	24	8.3	2,880				
	48	4.2	11,520				

Ordering Information

JE - 1 12 D M - G F

Insulation System:

Nil: Standard Class

F: F Class

Nil: AgNi

G: AgNi Gilded

O: AgNi Plated

N: AgSnO₂

S: AgSnO₂ Gilded

Nil: One Form C

M: One Form A

Coil Type:

D: Standard DC Coil

Coil Voltage: 03: 3V, 05: 5V, 06: 6V, 09: 9V, 12: 12V, 24: 24V, 48: 48V

Number of Pole: 1: One Pole




Type: JE

Classification


Model	JE	
Coil Sensitivity	Standard DC Coil	
Contact Form	1C	1A
Wash Tight Relay	JE - 1□□D - □	JE - 1□□DM - □

Dimension ($\leq 5\text{mm} \pm 0.2\text{mm}$, $> 5\text{mm} \pm 0.3\text{mm}$, the tolerance of PCB thru hole: $+0.1\text{mm}$)

JE-D






P.C.B. Layout




BOTTOM VIEW

JE-DM




P.C.B. Layout




BOTTOM VIEW

Reference Data


Temperature Rise (at 85°C)



Endurance(JE-DM)



Operate time



Release time

